

CS451 E & ET LOW VIBRATION



FEATURES

- Heavy duty frame.
- Continuous depth control with hand wheel and gauge.
- Water hose connector.
- Adjustable handle height, for all cutting depths.
- Handlebar equipped with vibration absorbers.
- Dust extraction hose plug (on CS451 ET).

BENEFITS

- Robust, low vibration level.
- Quick, easy and accurate setting.
- Allows wet cutting (for dry cutting when combined with CV360 dust extractor on CS451 ET (see p157)).
- Ergonomic working position.
- Improved working conditions.



CS451 ET BLADE GUARD

CS451 E

Item No. 701846 01973
EAN 13 Code 5450248 716822



7.5HP



5.5kW



400V 3~

Supply Voltage / Power	400V 3~ / 5.5kW (7.5Hp)
Fuse/Generator	16A / 14kVA
Blade x bore	Ø 450 x 25.4mm
Max. cutting depth	170mm
Dimensions (LxWxH)	1160 x 512 x 990mm
Water tank capacity (removable)	25 L
Tool speed RPM	2850 min ⁻¹
Starter	Electric
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	<2.5 m/s²
Sound power / pressure level	94 dB (A) / 80 dB (A)
Weight	105kg

CS451 ET

Item No. 701846 01972
EAN 13 Code 5450248 716815



7.5HP



5.5kW



400V 3~

Supply Voltage / Power	400V 3~ / 5.5kW (7.5Hp)
Fuse/Generator	16A / 14kVA
Blade x bore	Ø 350 x 25.4mm
Max. cutting depth	125mm
Dimensions (LxWxH)	1160 x 512 x 990mm
Water tank capacity (removable)	N/A
Tool speed RPM	2850 min ⁻¹
Starter	Electric
Raise and lower	Manual
Propelling	Push
Hand Arm Vibrations	<2.5 m/s²
Sound power / pressure level	94 dB (A) / 80 dB (A)
Weight	105kg

PRODUCT FEATURES



MAX CUT DEPTH
CS451 E



TWIN BLADE MOUNTING
(CS451 E ONLY)



MAX CUT DEPTH
CS451 ET



WATER HOSE CONNECTOR
(CS451 E ONLY)

DIAMOND BLADE RECOMMENDATIONS FOR CS451 E & ET



Substrate / Material	BETON	SILENCIO	ASPHALT	ALL MATERIALS
Recommended Product	EXTREME BETON	EXTREME BETON SILENCIO	EXTREME ASPHALT	PRO 4X4 EXPLORER
CS451 E				
Blade x Bore	450 x 25.4mm	450 x 25.4mm	450 x 25.4mm	450 x 25.4mm
Item No.	701846 02363	701846 31020	701846 94912	701846 02096
CS451 ET				
Blade x Bore	350 x 25.4mm	350 x 25.4mm	350 x 25.4mm	350 x 25.4mm
Item No.	701846 47790	701846 28997	701846 94537	701846 02093
Page reference	24	25	54	44